

## Product Parameters

Model	DHG-9030A
Power Supply(V/Hz)	220 50/60
Shell Material	Spray-paint Anti-corrosion
Liner Material	304 Stainless Steel
Temp. Range(°C)	RT+10~250/300
Temp. Stability(°C)	±1.0
Temp. Analysis(°C)	0.1
Working Temp(°C)	+5~40
Input Power (W)	850
Chamber Capacity (L)	40
Inner Dimension (W*D*H,mm)	340*310*340
Overall Dimension (W*D*H,mm)	620*580*480
Shelves (Pcs)	1
Time Range(min)	1~9999
Optional Configuration	Explosion-proof

TIPS: 110V/60Hz can be customized

## PRODUCT DISPLAY



### Micro-computer PID

1. High precision temperature control
2. Intelligent LCD display
3. Easy operation
4. Built in chip

PCD-C3000 Serials



### Product Features



#### 304 stainless steel shelf

- Anti-corrosion, durable
- High temperature resistance
- Good toughness

#### Large volume chamber

Cuboid chamber maximizes effective volume



#### Observation window

Double tempered glass windows for easy observation



#### Switch and Regulator

- Stepless speed regulation
- Adjust the size of the wind
- Easy to operate



## PRODUCT INTRODUCTION



## ON/OFF



## Handle